

PROFF WOODCARE PROFF COLOUR OIL



www.proffwoodcare.com

AREAS OF APPLICATION:

Proff Woodcare Proff Colour Oil is used for basic finishing of wood floors and woodwork in general. It produces a strong and wear resistant surface with enhancement of the wood grain. Proff Colour Oil stains and oils the woodwork at the same time.

APPLICATION OF MATERIAL:

Apply approximately one full coat of Proff Colour Oil to 10 - 12 square metres of wood floor lengthwise of the wood grain with a paint roller. Use a floor machine with beige or red pad to work the oil into the wood grain.

FINISH:

Proff Woodcare Proff Colour Oil produces a beautiful satin matt finish which can be maintained and repaired easily. The oiled floor and woodwork should be cleaned with Proff Woodcare Wood Floor Soap or Oil Refresher. For re-oiling we recommend Maintenance Oil or Maintenance Paste. An oiled floor is highly durable and easy to care for.

- * Ensures colour treatment and oiling of all wood species
- * Easy cleaning with Wood Floor Soap natural or white
- * Suitable for all wood species
- * Suitable for large commercial areas with high frequency of use

- In 12 different variations
- For oiling and colouring of wood floors and furniture
- For basic finish with floor machine or from hand
- Suitable for all wood species



PROFF WOODCARE PROFF COLOUR OIL



www.proffwoodcare.com

HOW TO DO

With a **Proff Colour Oil** you may colour and oil your wood at the same time. Proff Colour oil is suitable for use on all untreated interior floors and woodwork in general. Proff Colour Oil offers a strong protection against fluids and dirt and produces a hard wearing surface. Proff Colour Oil may be applied by hand or with a floor machine. The wood may be primed with one of the lye primers before the application of Proff Colour Oil. Proff Colour Oil enhances the natural grain of the wood. Proff Colour oil is a fast drying oil. Apply oil to sections of approx. 20 m² at the time. This allows enough time to work the oil well inside the wood grain.

Work Instruction:

1. Make sure that the floor is freshly sanded and cleaned with Intensive Wood Cleaner. Ensure that the floor is completely dry before starting the application of the oil. Moisture in wood should not exceed 12% relative moisture content.
2. Shake the bottle and ensure that all pigments are evenly distributed in material before application.
Apply 1 litre of oil to 10 to 15 m² of floor with a short haired paint roller or brush. Let the oil penetrate the wood grain for up to 15 min. and if dry spots appear, reapply oil. Now work the oil into the wood grain with floor machine mounted with beige or red pad. For areas not exceeding 15 m², polishing by hand with green pad is possible.
3. If not all oil could be worked into the wood grain, scrape the excess oil onto the next section of the floor or remove with cotton cloths. Continue in this way till complete area has been coated.
4. Now buff the complete area with a white pad under floor machine or by hand.
5. After a 6 hour pre-drying of the area, buff the whole area again with white pad under the machine possibly with a small application of oil to ensure a perfect finish of the wood. After 12 hours, the floor may be used with caution. Cover walkways with corrugated paper.
6. Leave the oiled area to dry for 48 hours. Do not expose the floor to water during drying time.
7. Use Proff Woodcare Wood Floor Soap or Proff Woodcare Oil Refresher mixed with water for regular cleaning. For later maintenance, apply same Proff Colour Oil as was used for basic treatment.

Risk of self ignition: Sanding dust and oil wetted cloths and pads must be disposed of either by soaking in water or burnt immediately after use. Risk of self ignition.

Disposal: Residues and containers are disposed of in accordance with local government regulations.